



SHACMAN F3000 8X4 Tipper Euro II SX3315DT386R-26m³

Engine	Make: WeiChai Power Diesel: 4-stroke direct injection diesel engine Engine model: WP10.380E22, Euro II emission 6-cylinder in-line with water cooling, turbo-charging and intercooling Maximum output: 380hp (280 Kw) at 2200 rpm Maximum torque: 1650 Nm at 1200-1600 rpm Number of cylinder: 6 Displacement: 9.726L Bore: 126mm Stroke: 130mm	
Clutch	Single-plate dry diaphragm-spring clutch, diameter 430 mm, hydraulically operating with air assistance	
Transmission	FAST transmission, model 10JSD180, manual syncromesh, 10F & 2R Ratio: 14.86 11.02 8.07 6.02 4.46 3.33 2.47 1.81 1.35 1 14.24® 3.19®	
Front Axle	9.5 ton MAN Front axle	
Rear Axle	16 ton MAN widen rear axle. Double reduction drive axle Ratio: 5.262	
Chassis	Frame: Section of 850*300(8+7) mm, reinforced sub-frame. Front suspension: 14-leaf semi-elliptical leaf springs with shock absorbers and stabilizer Rear Suspension: 12-leaf semi-elliptical leaf spring with stabilizer Fuel tank: 360L iron fuel tank capacity Spare wheel: 12R22.5	
Steering	ZF technology steering, domestic, hydraulic steering with power assistance Type: Hydraulic, right-hand driving	
Brakes	Service brake: dual circuit compressed air brake Parking brake (emergency brake): spring energy on rear axles Auxiliary brake: Exhaust brake	
Tyres & Wheels	Rims: 9.00x22.5, 10 hole-steel Tyres: 12R22.5	
Driver's Cab.	SHACMAN F3000 cab, hydraulic main seat, four points hydraulic suspension cabine with transverse shock absorber, electrical window lifter, A/C, single sleeper, with USB,can play radio with MP3 forma, steel bumper	
Electrics	Operating voltage: 24 V, negative grounded Batteries: 2 x 12 V, 165 Ah Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light VDO panel, active check control with indicators, with this instrument the daily manual checks on the vehicle and combined indicators of compressed air pressure, coolant temperature, engine oil pressure and battery charging	
Dimensions in mm	Wheel base Overall length Overall width Overall height	1800+3775+1400 10500 2500 3400
Weight in kg	Gross Vehicle Weight	70000
Performance	Maximum driving speed (km/h)	85
Performance	Economic driving speed (km/h)	45-60
Body	7400*2300*1500 (10mm bottom, 8mm side) , 180 cylinder, 5 longitudinal beams	
Front and rear lamp protection		
QH50 PTO		
Oil sump protection		
Reverse buzzer		
Jack (50T)		
Beacon light		
Oil-bath filter		
Anti-thief fuel tank and battery box		